

Rig 5

3000m Vertical

14 Loads-Summer 15 Loads-Winter

Draw works: TSM 500 (500hp) Rated for 112000 daN, Powered by 1-Detroit Series 60 (14L), w/6 speed Allison

transmission. Auxiliary braking by Eaton 224 disc brake.

Mud Pumps: 2- F-1000 triplex pump, powered by 2-Detroit Series 2000 (V-12-1005hp), w/XDR Pacific-Rim hydraulic clutch.

Max 125spm

Substructure: Hodgson Substructure. Hydraulic Self Leveling. KB-Ground 4.2m

Mast: Hodgson Telescopic Range 3 Single Mast. Hydraulically raising (Max static hook load 133000 daN-8 lines)

Top Drive: Warrior 175T Split Block Top Drive with 2-Speed Haglund and Electric HPU (Max Static Load 155000 daN).

Also has 8000 daN pull down capability.

Max TD rotary @ 180rpm Max torque @ 25000ft/lbs

Table: Rostel 17.5" (444mm) powered hydraulically-for auxiliary use only.

BOP's: 1-279mm X 21000kpa Spherical Annular Preventer

2-279mm X 21000kpa Townsend Pipe/Blind Single Gate Ram Preventer

Accumulator: 1-5 station 460L 21000kpa PLC Control Drilling accumulator, with N2 backup system.

Mud Tanks: 1-50m3, 4 Compartment circulating system, with additional pill tank and trip tank. 2-Agitators situated in

suction tanks, low pressure system powered by 2-5x6 Mission Magnum C-pumps, one with 14" impellor for

pumping aerated mud systems.

Solids Control: 1-Derrick FLC 504-3.5m3/min Capacity.

Water Tank/Doghouse: Hydraulic raising system-separate sub-storage room. Pason drilling recorder system. 60m3 useable water

tank.

Combination Building: 2-540kw Stamford powered by 2-630hp Detroit Series 60 (14L) engines. Monitoring provided by a

Woodward panel, which also synchronizes the two generators, and allows them to run in series. Also houses

a 12man change shack, and a 20000L fuel storage tank.

Catwalk: Skate Catwalk, with hydraulic skate, and leveling racks attached. Also houses nace trim 52mm&76mm

21000kpa Manifold.

Pipe Tubs: 3-Hydraulically controlled range 3 tubs

1-Loader Accessible range 3 tub

Tubulars: 3000m 102mm-4 FH, X-95 Drill pipe

8-159mm-4 ½ XH, Drill Collars 12-127mm-3 ½ IF, Drill Collars 25-102mm-4 FH, HWDP

Boiler: 1-100hp Williams&Davis Boiler with self contained 10000L fuel and 8m3 water tank.